

P/N 605 078 00
HARN, SIDE EJECT 960

J425A

1	39-22				
2	82-22				
3	54-18				
4					
5	93-22				
6	84-22				
7	83-22				
8	87-22				
9					
10					
11					
12					
13					
14	GND9-A/B				
15					
16	22-22				
17	55-22				
18	33-22				
19					

P425A
REFERENCE
APPROPRIATE
WIRING DIAGRAM

E1

E2

E3

GND10-A

P120

4	39-22				
5	82-22				
9	93-22				
10	84-22				
11	83-22				
12	87-22				
6	35-22				
7	36-22				
8	37-22				
13					
14					
3	22-22				
15	55-22				
1	33-22				
2	33-22				
16	55-22				

J120

4	HOPPER PROBE OUT	
5	HOPPER MOTION	
9	COIN OUT	
10	HOPPER BRAKE	
11	HOPPER DIRECTION	
12	HOPPER SAFETY	
6	FULL	
7	TWO THIRDS	
8	ONE THIRDS	
13	COIN TOLERANCE	
14	GROUND	
3	+13VDC	
15	GROUND	
1	+25VDC	
2	+25VDC	
16	GROUND	

P/N 350 032 90
MOTOR-HPR, 24V DC, 25RPM

B1

P123

1		
2		

J123

1	OUT B (-H MOTOR)	
2	OUT A (+H MOTOR)	

P/N 379 063 00
OPTIC ASSY-SECURE,AC

	11-28	1	
	22-28	2	
	33-28	3	
	44-28	4	
	55-28	5	
	66-28	6	

J122

1	VCC	
2	COLLECTOR 1	
3	CATHODE 1	
4	COLLECTOR 2	
5	CATHODE 2	
6	GND	

NOT USED

J121

1	+5VDC	
2	ANODE SUPPLY	
3	GND	
4	HOPPER MOTION	

DWG NO 820 490 08